

United States Patent

Yukitake et al.

Patent Number: [11]

5,745,182

Date of Patent: [45]

Apr. 28, 1998

f 541	METHOD FOR DETERMINING MOTION
	COMPENSATION

[75] Inventors: Takeshi Yukitake; Shuji Inoue, both of

Yokohama, Japan

Assignee: Matsushita Electric Industrial Co., 1731

Ltd., Osaka. Japan

[21] Appl. No.: 278,010

[30]

Jul. 20, 1994 [22] Filed:

Related U.S. Application Data

Division of Ser. No. 970,046, Nov. 2, 1992, Pat. No. [62] 5,369,449. Foreign Application Priority Data

	z. 8, 1991 l. 9, 1992	[JP]	Japan Japan	3-293004
[51]	Int. Cl.6			H04N 7/32
[52]	U.S. CI.			
[58]	Field of	Search	ı	348/413, 416.
				400-402, 407, 409-412, 384,
		390. 4	115: 38	2/232, 236, 238; H04N 7/137

[56] References Cited

U.S. PATENT DOCUMENTS

	Kaneko et al	
4,864.294 4,989,089	Gillard . Chantelou et al	•

(List continued on next page)

FOREIGN PATENT DOCUMENTS

0395271A2 10/1990 European Pat. Off. .

0395440A2	10/1990	European Pat Off.
0447068A2	9/1991	European Pat. Off
0484140A2	5/1992	European Par Off.

OTHER PUBLICATIONS

A. Puri, et al, "Video Coding with Motion-Compensated Interpolation for CD-ROM Applications", Signal Processing. Image Communication, vol. 2, No. 2, pp. 127-144, Aug. 1990.

K. Kinuhata, et al. "Universal Digital TV Codec -Unicodec", 7th International Conference on Digital Satellite Communications. May 1986, pp. 281-288.

(List continued on next page.)

Primary Examiner-Richard Lee Attorney, Agent, or Firm-Watson Cole Stevens Davis, P.L.L.C.

[57] ABSTRACT

A method for predicting motion compensation for determining of an input image based on a motion vector of the input image from this input image to a reference image which has been sampled at a first set time, and the method includes calculating a motion vector of the input image based on a move, at a second set time, of a block unit which is a part of the input image and consists of a plurality of pixels, and calculating a motion vector of the reference image based on a move, at the first set time, of a block unit which is a part of the reference image and consists of a plurality of pixels. Move compensation of the input image is calculated both from the motion vector of the input image and from the motion vector of the reference image, to thereby realize a method for determining motion compensation with high precision.

3 Claims, 6 Drawing Sheets

